



INFORMATION SHEET FOR AIR CONDITIONERS, EXCEPT DOUBLE DUCTS AND SINGLE DUCTS⁽⁵⁾

As by Comission Communication in the framework of ecodesign requirements for air conditioners and comfort fans (EU Regulation no. 206/2012) and of energy labelling of air conditioners - (EU Regulation no. 626/2011).

MODEL : AQ OUT HY 26 / AQ WNI 12(x3)

Function to which information applies				If information applies to heating: heating season to which information relates.			
Cooling	Y	Heating (Average)(-10°C)				Y	
Heating	Y	Heating (Warmer)(+2°C)				na	
		Heating (Colder)(-22°C)				na	
Item	symbol	value	unit	Item	symbol	value	unit
Design load				Seasonal efficiency			
Cooling	Pdesignc	6,5	kW	Cooling	SEER	6,5	-
Heating (Average)(-10°C)	Pdesignh	6,4	kW	Heating (Average)(-10°C)	SCOP (A)	4,0	-
Heating (Warmer)(+2°C)	Pdesignh	na	kW	Heating (Warmer)(+2°C)	SCOP (W)	na	-
Heating (Colder)(-22°C)	Pdesignh	na	kW	Heating (Colder)(-22°C)	SCOP (C)	na	-
Declared capacity (*) for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj				Declared Energy efficiency ratio (*) for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj = 35°C	Pdc	6,50	kW	Tj = 35°C	EERd	3,75	-
Tj = 30°C	Pdc	4,99	kW	Tj = 30°C	EERd	5,67	-
Tj = 25°C	Pdc	3,30	kW	Tj = 25°C	EERd	7,39	-
Tj = 20°C	Pdc	2,43	kW	Tj = 20°C	EERd	9,02	-
Declared capacity (*) for heating / Average season, at indoor temperature 20°C and outdoor temperature Tj				Declared Coefficient of Performance (*) for heating / Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	5,92	kW	Tj = -7°C	COPd	3,09	-
Tj = 2°C	Pdh	3,70	kW	Tj = 2°C	COPd	4,12	-
Tj = 7°C	Pdh	2,26	kW	Tj = 7°C	COPd	4,83	-
Tj = 12°C	Pdh	1,41	kW	Tj = 12°C	COPd	4,59	-
Tj = bivalent temperature	Pdh	5,92	kW	Tj = bivalent temperature	COPd	3,09	-
Tj = operating limit temperature	Pdh	4,26	kW	Tj = operating limit temperature	COPd	1,84	-
Declared capacity (*) for heating / Warmer season, at indoor temperature 20°C and outdoor temperature Tj				Declared Coefficient of Performance (*) for heating / Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj = 2°C	Pdh	na	kW	Tj = 2°C	COPd	na	-
Tj = 7°C	Pdh	na	kW	Tj = 7°C	COPd	na	-
Tj = 12°C	Pdh	na	kW	Tj = 12°C	COPd	na	-
Tj = bivalent temperature	Pdh	na	kW	Tj = bivalent temperature	COPd	na	-
Tj = operating limit temperature	Pdh	na	kW	Tj = operating limit temperature	COPd	na	-
Declared capacity (*) for heating / Colder season, at indoor temperature 20°C and outdoor temperature Tj				Declared Coefficient of Performance (*) for heating / Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	na	kW	Tj = -7°C	COPd	na	-
Tj = 2°C	Pdh	na	kW	Tj = 2°C	COPd	na	-
Tj = 7°C	Pdh	na	kW	Tj = 7°C	COPd	na	-
Tj = 12°C	Pdh	na	kW	Tj = 12°C	COPd	na	-
Tj = bivalent temperature	Pdh	na	kW	Tj = bivalent temperature	COPd	na	-
Tj = operating limit temperature	Pdh	na	kW	Tj = operating limit temperature	COPd	na	-
Tj = -15°C	Pdh	na	kW	Tj = -15°C	COPd	na	-
Bivalent temperature				Operating limit temperature			
Heating (Average)	Tbiv	-7	°C	Heating (Average)	Tol	-22	°C
Heating (Warmer)	Tbiv	na	°C	Heating (Warmer)	Tol	na	°C
Heating (Colder)	Tbiv	na	°C	Heating (Colder)	Tol	na	°C
Power consumption of cycling				Efficiency of cycling			
Cooling	Pcycc	na	kW	Cooling	EERcyc	na	-
Heating	Pcych	na	kW	Heating	COPcyc	na	-
Degradation coefficient cooling(**)	Cdc	0,25	-	Degradation coefficient heating(**)	Cdh	0,25	-
Electric power input in power modes other than "active mode"				Seasonal electricity consumption			
Off mode	P _{OFF}	na	W	Cooling	Q _{CE}	350	kWh/a
Standby mode	P _{SB}	1,225	W	Heating (Average)(-10°C)	Q _{HE} /A	2344	kWh/a
Thermostat-off mode	P _{TO}	1,225	W	Heating (Warmer)(+2°C)	Q _{HE} /W	na	kWh/a
Crankcase heater mode	P _{ck}	30	W	Heating (Colder)(-22°C)	Q _{HE} /C	na	kWh/a
Capacity control type				Other items			
Fixed	N	Sound power level (indoor/outdoor)				L _{WA}	45/64
Staged	N	Refrigerant type				R410A	
Variable	Y	Global warming potential				GWP	2087,5
		Rated air flow (indoor/outdoor)				600/2400	KgCO ₂ eq.
For more detailed information				EUROFRED, S.A. -MARQUÉS DE SENTMENAT, 97 08029 BARCELONA - T.: + 34 934 199 797 F.: + 34 934 198 686 www.eurofred.es			

(5) For multisplit appliances, data shall be provided at a *Capacity ratio* of 1.

(**) If default Cd=0,25 is chosen, then results from cycling tests are not required. Otherwise either the heating or cooling cycling test value is required